

Package Contents




Key Light with Articulating Arm ×1



Connecting Rod with Buckle ×1




Remote Control ×1




Power Adapter ×1

Setup Instructions

1. Attach and secure the mounting clamp to the desktop. Loosen the locking mechanism on the desk mount, insert the articulating arm piece, and then tighten to secure. Connect the light to a power source to begin using.



Use Instructions



As shown in the figure, the light assembly can be adjusted flexibly to provide an optimal lighting angle.

1. Control Panel



"⏻"Power Button:
When the power indicator lights up in white, tap it to power the panel light on/off (the indicator will turn off when the light is on).

"☼-"Brightness Down Button:
When the round panel light is turned on and its brightness level is set to the lowest level, the button lights up in white to indicate the current brightness is at the minimum (10 brightness levels available).

"☼+"Brightness Up Button:
When the round panel light is turned on and its brightness level is set to the highest level, the button lights up in white to indicate the current brightness is at the highest setting (10 brightness levels available).

"M"Color Temperature Switch Button:
When the light is on, you can cycle through 5 different color temperatures. (The indicator light of the button "M" changes color to match the current color temperature of the light itself.)

"⏲"Timer Button:
When the timer is set, the button lights up white for 60 minutes and blue for 30 minutes. If the indicator light is off, the timer is not active.

EN

EN

Use Instructions

2. Remote Control



The "⏻"Power Button:
controls the on/off function of the key light.

" + " Brightness Up Button:
When the light is on, each tap increases the brightness by one level, up to a total of 10 levels.
(A long press allows for stepless increasing of brightness level).

" — " Brightness Down Button:
When the light is on, each tap decreases the brightness by one level, with a total of 10 levels. (A long press allows for stepless dimming).

" K+ "Color Temperature Increase Button:
When the light is on, each tap increases the color temperature by 1 level (with 5 levels to cycle through).

" K— " Color Temperature Decrease Button
When the light is on, each tap decreases the color temperature by 1 level (with 5 levels to cycle through).

"◷" Timer Button:
Press the touch timer key repeatedly while the main light is on to cycle through timer settings: white light for automatic light off after 60 minutes, blue light for automatic light off after 30 minutes, or no light for no timer function.

" ⏱ " Delay Light-off Button:
Press this button when the light is on. The brightness will auto adjust to 30% and go out after 1 minute.

Note: Remove the insulation tab in the battery compartment before using the remote.

Notes

1. Do not subject the product to any impact or collision.
2. To protect your eyesight, please avoid looking directly at the light.
3. Turn off the power when not in use.
4. Secure the desk mount tightly to prevent accidental falls and damage.
5. Please use only the included power adapter to power the device. Using an incompatible adapter may cause fire or explosion.
6. Do not heat, disassemble, puncture the device or the battery. Exposing either to fire or direct sunlight for long periods may cause battery damage.

Specifications

Model	R18
Material	ABS, PC, Acrylic, Zinc Alloy
Rated Power	18W
Power Input	DC24V 0.75A
Number of LEDs	84
CRI	95
Power Supply	Detachable DC 5.5 Power Connector
Color Temperature	3000-6500K
Max Illumination	1380LUX@0.5m
Panel Light Weight	0.87kg
Max Assembled Height	109cm